

COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

WARNING

This material has been reproduced and communicated to you by or on behalf of
The University of Adelaide pursuant to Part VB of the Copyright Act 1968 (the Act).

The material in this communication may be subject to copyright under the Act.
Any further reproduction or communication of this material by you may be the
subject of copyright protection under the Act.

Do not remove this notice.

External Copyright permission (if applicable)



Predicting weld cooling rates and the onset of failure during in-service welding

Prakash N. Sabapathy

B.E. Hons. (Adelaide), 1995

The University of Adelaide

Department of Mechanical Engineering

South Australia 5005

Submitted for the degree of Doctor of Philosophy, 1st February 2002.

Predicting weld cooling rates and the onset of failure during in-service welding

ABSTRACT

A comprehensive numerical simulation of the in-service welding of high pressure gas pipelines has been developed. A system has been established for predicting the safe, suitable welding conditions at which in-service manual metal arc welding using low-hydrogen electrodes can be achieved on thin, high-strength pipes with flowing pressurised natural gas. The two main concerns of in-service welding are: the possibility of excessively hard heat affected zone microstructure due to fast cooling rates, and the possibility of failure of the pipe wall due to localised heating from the welding arc.

The finite element method was applied to calculate the cooling rates from circumferential fillet welds and branch on pipe welds. Initial development considered approximating the process in two dimensions, but was quickly rejected in favour of three-dimensional conduction only models which included temperature dependent material properties. The welding arc was approximated as a three-dimensional heat flux distribution function. Numerical simulations were validated using both laboratory and field trials. The experiments involved welding on a water cooled device which simulated in-service welding cooling conditions in a laboratory, while a second experiment involved welding onto a flow-loop attached to an actual operating pipeline. The results from the experiments were used to define the heat source distribution, to account for weld weaving, and shallow penetration welding. Weld pool flow was not calculated, but the effects of weld pool convection were included in the heat source.

An investigation was made to calculate the limits at which in-service welding can produce safe, mechanically sound welds under a combination of low wall thickness pipe and high pressure. Initial development consisted of calculating pipe wall deflection using three-dimensional thermal elastic-plastic models. Such models are very expensive computationally, which led to the development of a new model to calculate the limits of in-service

welding. This ‘equivalent cavity’ model primarily used a thermal field, as calculated from the thermal models, to calculate the maximum pressure at which a weld can be deposited. The accuracy and feasibility of the equivalent cavity model was determined by comparing its predictions with published data relating to pipe wall failure, and numerical simulations of pipe wall failure using thermal elastic-plastic finite element models.

In combination, the thermal and pipe wall failure models offer valuable savings during the design stage of in-service welding. While the models form an accurate system to predict weld cooling rate and the possibility of pipe wall failure, they avoid the cost of traditional trial and error experimentation, often chosen for the testing phase of in-service welding.

Contents

1	Significance and objective	1
1.1	Overview	1
1.2	Industrial significance of in-service welding	2
1.3	Technical challenges to in-service welding	6
1.4	Research strategy	8
2	Literature review	13
2.1	Introduction	13
2.2	In-service welding	14
2.2.1	Post-weld hardness	14
2.2.1.1	Summary & gaps in knowledge	20
2.2.2	Burnthrough	23
2.2.2.1	Summary & gaps in knowledge	35
2.3	Thermal modelling	40
2.3.1	Introduction	40
2.3.2	Analytical solutions	41

2.3.2.1	Summary	45
2.3.3	Numerical solutions	47
2.3.4	Summary & gaps in knowledge	62
3	Thermal modelling	70
3.1	Introduction	70
3.1.1	Mesh generation	71
3.1.2	Boundary conditions	73
3.1.3	Material properties	75
3.1.4	Solution parameters	78
3.1.5	Data extraction	78
3.2	Circumferential fillet welding	80
3.2.1	Introduction	80
3.2.2	Mesh generation	80
3.2.3	Transient analysis	84
3.2.3.1	Introduction	84
3.2.3.2	Mesh generation	85
3.2.3.3	Calculation of heat flux	87
3.2.3.4	Boundary conditions	94
3.2.4	Quasi-steady-state analysis	95
3.2.4.1	Introduction	95

3.2.4.2	Mesh generation	96
3.2.4.3	Calculation of heat flux	97
3.2.4.4	Material properties	98
3.2.4.5	Boundary conditions	99
3.3	Branch on pipe welding	101
3.3.1	Introduction	101
3.3.2	Mesh generation	102
3.3.3	Transient analysis	110
3.3.3.1	Introduction	110
3.3.3.2	Mesh	111
3.3.3.3	Calculation of heat flux	113
3.3.3.4	Boundary conditions	118
3.4	Internal pipe convection	118
3.4.1	Introduction	118
3.4.2	Flow regime	120
3.4.3	Non-dimensional estimation of heat transfer coefficient	123
3.4.3.1	Introduction	123
3.4.3.2	Calculation of heat transfer coefficient	123
3.4.3.3	Sensitivity analysis of thermal models to Sieder & Tate non-dimensional approximation	126
3.4.4	Numerical approach	127

3.4.4.1	Introduction	127
3.4.4.2	Analysis	127
3.4.4.3	Future work	130
3.4.5	Conclusions	130
3.5	Heat source development	130
3.5.1	Introduction	130
3.5.2	Derivation	131
3.5.3	Discussion	134
3.5.4	Conclusions	138
4	Experiments	139
4.1	Introduction	139
4.2	Laboratory simulation	141
4.2.1	Initial experiment: mechanised welding	144
4.2.2	Manual in-service welding laboratory simulation	147
4.2.2.1	Experimental equipment	147
4.2.2.2	Experimental plan	150
4.2.3	Analysis of experimental results	153
4.2.3.1	Variation of heat input with welding position	153
4.2.3.2	Variation of weld penetration with welding position	154
4.2.3.3	Variation of weld penetration with heat input	159

4.2.4 Conclusions	160
4.3 Field experiments	162
4.3.1 Introduction	162
4.3.2 Test material	163
4.3.3 Experiment methodology	164
4.3.4 Analysis data collection	166
4.3.5 Data analysis	175
4.3.5.1 Variability of heat input	175
4.3.5.2 Maximum penetration depth variation with heat input . .	179
4.3.5.3 Maximum HAZ depth variation with heat input	182
4.3.5.4 Weld cooling time variation with heat input	185
4.3.6 Variation of HAZ and penetration depth with position	189
4.3.6.1 Maximum HAZ depth variation with position	189
4.3.6.2 Penetration depth variation with position	189
4.3.6.3 Variation of HAZ and penetration depth for a given weld pass	192
4.3.7 Conclusions	193
4.4 Weld bead geometry model	195
4.4.1 Introduction	195
4.4.2 Derivation of model	196
4.4.2.1 Parabolic reinforcement	198

4.4.2.2 Weld bead area	199
4.4.2.3 Welding angle	200
4.4.3 Comparison with field tests	203
4.4.3.1 Introduction	203
4.4.3.2 Weld bead geometry: field experiments	203
4.4.3.3 Welding angle	203
4.4.3.4 Weld bead area	206
4.4.4 Conclusions	208
5 Validation of in-service welding thermal model	210
5.1 Introduction	210
5.2 Validation of in-service welding models	212
5.2.1 Introduction	212
5.2.2 Penetration depth	212
5.2.3 HAZ depth	216
5.2.4 Weld cooling time	219
5.2.5 Hardness comparison	222
5.3 Conclusion	227
6 Pipe wall failure	229
6.1 Introduction	229
6.2 Examining pipe wall failure	232

6.3 Thermal elastic-plastic stress analysis of in-service welding	234
6.3.1 Introduction	234
6.3.2 Analysis	235
6.3.3 Results	236
6.3.4 Discussion	239
6.3.5 Conclusions	240
6.4 Verification of B31G corrosion cavity model	240
6.4.1 Introduction	240
6.4.2 Comparison	241
6.4.3 Analysis	242
6.4.4 Results & Discussion	245
6.4.4.1 Varying longitudinal cavity length	245
6.4.4.2 Varying circumferential cavity length	247
6.4.4.3 Cavity depth	248
6.4.5 Conclusions and recommendations	253
6.5 Verification of equivalent cavity model	254
6.5.1 Introduction	254
6.5.2 Results & comparison	254
6.5.3 Discussion	259
6.5.4 Conclusions	262
6.6 Conclusions and future work	262